



Crystals Limited


30-Series General Oscillator Specifications

Description	Min	Typ	Max	Unit
Frequency Range	2		48	MHz
Overall Stability (+/-)	20		100	ppm
Supply Voltage (+/-10%)	1.8		5	V
Operating Temperature Range	0~70		-40~+85	Deg C
Capacitive Load on Output		15	50	pF
TTL Load on Output	1		10	TTL
Supply Current:				
5V 2.0-48MHz			30	mA
3.3V 2.0-48MHz			30	mA
Output Voltage :				
High (5Vdd)	4.5			V
High (3.3Vdd)	2.97			V
Low (5Vdd)			0.5	V
Low (3.3Vdd)			0.33	V
Symmetry	40:60	45:55	48:52	%
Jitter		1		pS
Rise/Fall time (frequency dependant)			10	nS
Start up Time			10	mS


AEL Crystals Ltd. Reserve the right to amend specifications without notification. Please ensure you have the latest issue

*please contact our Sales Office for further options

TITLE	AEL 30-series oscillator
Part Number	Contact Sales Office
Stock Number	Contact Sales Office
Issue Date	17/07/2007
Issue Number	5



Recommended Solder Pad Layout



Pin Assignments

Pin 1	Tri-State (301-)
Pin 2	Ground
Pin 3	Output
Pin 4	+V DC

Tri-State Voltages

N.C	Output Active
>2.2V	Output Active
<0.8V	Output Disabled

(Pin 1 has internal pull up resistor to allow it to float High)

Options and How to Specify

Pin 1:	AEL30
Supply voltage:	1=E/D
Stability* (+/-ppm):	0=5V, 3=3.3, 2=2.5V, 1=1.8V
Temperature range:	C=100, B=50, A=25
	S=0~+70, I=-40~+85C
	e.g. AEL3010AI 30MHz = E/D, 5V, +/-25ppm, -40~+85C, 30MHz



Crystals Limited

Module "D", Airtech II
Jenner Road, Manor Royal
Crawley RH10 9GA

© Not to be reproduced without permission of AEL Crystals Ltd