

**DSM/DSB**

D-SUB SPACERS

Part No		"L2" mm	"M1" mm	"M2" mm	"H" mm	length mm	"L1" mm
mild steel	brass						
DSB-6-M3-M3	DSM-6-M3-M3	6.0	M3	M3	5.0	5.0	3.0
DSB-6-4.40-M3	DSM-6-4.40-M3	6.0	4.40	M3	5.0	5.0	3.5
DSB-6-M3-4.40	DSM-6-M3-4.40	6.0	M3	4.40	5.0	5.0	3.0
DSB-6-4.40-4.40	DSM-6-4.40-4.40	6.0	4.40	4.40	5.0	5.0	3.5
DSB-8-M3-M3	DSM-8-M3-M3	8.0	M3	M3	5.0	5.0	3.0
DSB-8-4.40-M3	DSM-8-4.40-M3	8.0	4.40	M3	5.0	5.0	3.5
DSB-8-M3-4.40	DSM-8-M3-4.4	8.0	M3	4.40	5.0	5.0	3.0
DSB-8-4.40-4.40	DSM-8-4.40-4.40	8.0	4.40	4.40	5.0	5.0	3.5
DSB-12-M3-M3	DSM-12-M3-M3	12.0	M3	M3	5.0	5.0	3.0
DSB-12-4.40-M3	DSM-12-4.40-M3	12.0	4.40	M3	5.0	5.0	3.5
DSB-12-M3-4.40	DSM-12-M3-4.40	12.0	M3	4.40	5.0	5.0	3.0
DSB-12-4.40-4.40	DSM-12-4.40-4.40	12.0	4.40	4.40	5.0	5.0	3.5

Material: Brass CuZn39Pb3/mild steel  
 Plating: G3 E nickel to DIN 267  
 Max. Torque: 430 N / mm<sup>2</sup>  
 Tolerance: ± 0,1 mm  
 Std. Pk.: 100 pcs.

Note:

DSB	6	4.40	M3	5
Part	Female	Female	Male	Length
	Thr.-Length	Thread	Thread	