



Product Data Sheet

CILS-9300Y Yellow Matt Polyester

MATERIAL	Yellow Matt Polyester with Durable Laser Imprintable Top Coating.
ADHESIVE	Pressure sensitive permanent solvent acrylic.
GENERAL DESCRIPTION	Designed as a carrier of laser imprinted text, for use in a wide range of harsh environments. Excellent resistance to abrasion, heat, moisture, chemicals, weathering, oils, hydraulic fluids and oils. Good dimensional stability. Barcode printable.
TOTAL THICKNESS	75 Microns
SERVICE TEMPERATURE RANGE	-55°C to +155°C
MINIMUM APPLICATION TEMP.	5°C (40°F).
STORAGE STABILITY	2 Years stored at 10°C and 25°C and 35% to 65% relative humidity.

Important Notice to Purchaser: All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties, of merchantability and fitness for purpose: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. NEITHER SELLER NOR MANUFACTURER SHALL BE LIABLE EITHER IN TORT OR IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL, OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR THE INABILITY TO USE THE PRODUCT. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by offices of seller and manufacturer.