

7 ports USB3 hub til DIN montering



Product codes:

Reference: USB3HUB7DIN

Product short description:

7-Port USB3.0 hub med Surge Protection og DIN RAIL monterings kit

Product features:

Dimensioner: 4.80"(L)x2.16"(W)x1.71"(H) (12.20x5.50x4.35 cm)

USB: Supports keyboard, mouse, monitor, scanner, printer, PC Camera, telephone, DVD drive, joystick, virtual reality helmet, modem, PBX and many more USB devices

Driftstemperatur: -20 to 85C (-4 to 185F)

Understøtter: USB3.0, USB2.0, or USB1.1 Ports USB3.0 ports

DC Input: +7~48 VDC via terminal block

I/O: Supports 7 external USB3.0 Type-A connectors and 1 USB3.0 Type-B Upstream connector. Supports a 2-pin Terminal Block Connector for external power input from AC adapter

Product description:

- Compliant with USB Specification Revision 3.0 - Metal Case with DIN RAIL Mounting Kit for Industrial Critical Applications - Built-in RISC-like USB3.0 Hub Controller -

DANBIT

Provides 7 Downstream USB3.0 Facing Ports - Supports 5Gbps (Super-speed), 480Mbps (High-speed), 12Mbps (Full-speed) and 1.5Mbps (Low-speed) Speed - Supports Surge and 15KV ESD Protection for Each Port - Supports +7~48V DC Wide Range Self-power Input - Multi Transaction Translators (TT) per Hub - Supports Wide Range Self-power Input - Support USB Battery Charging: CDP and DCP modes - Supports USB Screw-Lock Cable Mechanism System: For Systems with USB3.0, USB2.0, or USB1.1 Ports USB3.0 ports Provides 7 USB downstream ports which managing up to 5Gbps: Compliant with USB Specifications 3.0 Provides 7 USB3.0 Downstream Facing Ports Supports 5Gbps, 480Mbps, 12Mbps and 1.5Mbps Speed Supports Multi Transaction Translators per Hub Supports Wide Range Input Self-power Mode from Terminal Blocks Supports USB Screw-lock Cable Mechanism Supports +7~48V DC Wide Range Self-power Input Supports 15KV ESD Protection for Each Port. USB Devices: Supports keyboard, mouse, monitor, scanner, printer, PC Camera, telephone, DVD drive, joystick, virtual reality helmet, modem, PBX and many more USB devices I/O Hardware: Supports 7 external USB3.0 Type-A connectors and 1 USB3.0 Type-B Upstream connector. Supports a 2-pin Terminal Block Connector for external power input from AC adapter Environmental: Operating Temp.: 0 to 70C (32 to 158F) Storage Temp: -20 to 85C (-4 to 185F) Operating Humidity: 5 to 95% RH Dimensions: 4.80"(L)x2.16"(W)x1.71"(H) (12.20x5.50x4.35 cm)

Product attributes: