

CERAMIC BODY

3AB Slo-Blo® Type Fuse



Ceramic body construction permits higher interrupting ratings and voltage ratings. Ideal for applications where high current loads are expected.

ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Ampere Rating	Opening Time
110%	1/100-30	4 hours, Minimum
135%	1/100-30	1 hour, Maximum
200%	1/100-3.2	5 sec., Min. ; 30 sec. Max.
	4-30	5 sec., Min. ; 60 sec. Max.

AGENCY APPROVALS: Listed by Underwriters Laboratories from 1/4 through 10 amperes. Certified by CSA from 1/4 through 30 amperes.

AGENCY FILE NUMBERS: UL E10480, CSA LR 29862.

FUSES TO MIL SPEC: See F03B cartridge type in Military Section.

PATENTED


ORDERING INFORMATION:

Cartridge Catalog Number	Axial Lead Catalog Number	Ampere Rating	Voltage Rating	Nominal Resistance Cold Ohms	Nominal Melting I ² t A ² Sec.
326.010	325.010	1/100	250	3300	0.00148
326.031	325.031	1/32	250	330	0.0110
326.062	325.062	1/16	250	91.0	0.0276
326.100	325.100	1/10	250	33.3	0.0870
326.125	325.125	1/8	250	22.3	0.100
326.150	325.150	15/100	250	15.3	0.143
326.175	325.175	.175	250	8.84	0.220
326.187	325.187	3/16	250	7.67	0.230
326.200	325.200	2/10	250	6.72	0.213
326.250	325.250	1/4	250	4.40	0.432
326.300	325.300	3/10	250	3.20	0.690
326.375	325.375	3/8	250	2.14	1.20
326.400	325.400	4/10	250	1.92	1.33
326.500	325.500	1/2	250	1.29	2.50
326.600	325.600	6/10	250	0.940	3.90
326.700	325.700	7/10	250	0.716	6.42
326.750	325.750	3/4	250	0.636	7.00
326.800	325.800	8/10	250	0.568	8.20
326 001	325 001	1	250	0.386	16.3
326 01.2	325 01.2	1 1/10	250	0.284	22.0
326 1.25	325 1.25	1 1/4	250	0.266	24.0
326 01.5	325 01.5	1 1/2	250	0.196	40.1
326 01.6	325 01.6	1 3/10	250	0.175	45.0
326 002	325 002	2	250	0.120	80.0
326 02.5	325 02.5	2 1/2	250	0.0830	136.0
326 02.8	325 02.8	2 3/10	250	0.0690	170.0
326 003	325 003	3	250	0.0600	200.0
326 03.2	325 03.2	3 1/10	250	0.0535	214.0
326 004	325 004	4	250	0.0755	9.71
326 005	325 005	5	250	0.0518	25.0
326 6.25	325 6.25	6 1/4	250	0.0343	60.4
326 007	325 007	7	250	0.0225	47.3
326 008	325 008	8	250	0.0191	67.1
326 010	325 010	10	250	0.0131	137.0
326 012	325 012	12	250	0.0066	129.0
326 015	325 015	15	250	0.0049	245.0
326 020	325 020	20	250	0.0033	575.0
326 025	325 025	25	125	0.0024	1030.0
326 030	325 030	30	125	0.0019	1690.0



326 000 Series

325 000 Series



Axial Lead Material: Solder coated copper.

Average Time Current Curves

