


PCB Layout



Specifications:

Current Rating:3.0A AC/DC
 Voltage Rating:250V AC/DC
 Contact Resistance:20m ohm Max
 Insulation Resistance:1000M ohm Min
 Withstanding Voltage:600V AC For one Minute
 Operating Temperature Range:-40°C To +105°C
 Materials:

Insulator:High Temp.Plastic(Nylon 6T UL94V-0)
 Insulator Color:Black
 Contact:Copper Alloy
 Plating:Gold Plated

How To Order

2213S-XXG-BK-F2

- Lead Free
- BK:Black
- G:Gold Plated
- No.Of Positions
- Straight Type

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:	 繼德工業股份有限公司 Neltron Industrial Co., Ltd.	DESCRIPTION: 2.54mm Pin Header Double Row Straight Type	SIZE A4
E			Cel King	.X=±0.20				
D			CHECKED:	.XX=±0.15				
C			Jeremy Liu	UNIT: MM				
B			APPROVAL:	SCALE: 1:1	DESCRIPTION:	SIZE		
A	17-Jan-2006	(PC0001)	Cel King	Mike Wu	SHEET: 1 / 1	PART NO:	A4	
REV	DATE	FILE	BY	PROJECTION:		2213S-XXG-BK-F2		

DRAWN:	GENERAL TOLERANCE:
Cel King	.X=±0.20
CHECKED:	.XX=±0.15
Jeremy Liu	UNIT: MM
APPROVAL:	SCALE: 1:1
Mike Wu	SHEET: 1 / 1
PROJECTION:	

DESCRIPTION:	SIZE
2.54mm Pin Header Double Row Straight Type	A4
PART NO:	
2213S-XXG-BK-F2	