



FrontCom® Micro

- Cat.6A
- IP 65

FrontCom® Micro



Markers, FrontCom® Micro



Technical data

Category
Protection class
Housing material
Colour
Shielding
Installation
Plugging cycles

Cat. 6A / Class E_A (IEC 11801 PDAM Am 1.2 2007)
IP 65 gemäß EN 60529
PA; UL 94: V-0 (Protective cap NBR)
black
360° shield contact
to electrical cabinet, distribution board or control panel
750 plugging cycles for connectors, according to IEC 60603-7

Application:

Weidmüller's FrontCom® Micros are your best choice when you need an IP65 connection at the control panel, electrical cabinet or distribution board.

The differences:

- 1018790000: Coupling insert for RJ45 to RJ45, straight version
- 1018810000: RJ45 module insert for connecting AWG 26 – AWG 22 wires; colour coding according to EIA/TIA 568 A
- 1018820000: RJ45 module insert for connecting wires from AWG 26 to AWG 22; colour coding according to EIA/TIA 568 B
- 1018830000: RJ45 module insert for connecting wires from AWG 26 to AWG 22; colour coding according to industrial Ethernet
- 1018840000: Coupling insert for USB to USB

Ordering data

Product description
FrontCom® Micro RJ45 Coupling
FrontCom® Micro RJ45, TIA-A Module
FrontCom® Micro RJ45, TIA-B Module
FrontCom® Micro RJ45, Industrial Ethernet Module
FrontCom® USB Coupling
SwitchMark holder
SwitchMark markers, white

Type	Order No.
IE-FCM-RJ45-C	1018790000
IE-FCM-RJ45-FJ-A	1018810000
IE-FCM-RJ45-FJ-B	1018820000
IE-FCM-RJ45-FJ-P	1018830000
IE-FCM-USB-A	1018840000
SM-H 27/18	1716630000
SM 27/18 MC	1699860000

Note: Refer to Catalogue 7 for additional variants.